

Perfil A

Número da correia	Circunf. Externa (pol)	Circunf. Externa (mm)	Peso por seção (lb)	Peso por seção (g)
A26K	28,0	711,2	0,26	118
A31K	33,0	838,2	0,29	132
A33K	35,0	889,0	0,31	141
A35K	37,0	939,8	0,33	150
A38K	40,0	1016,0	0,35	159
A40K	42,0	1066,8	0,36	163
A42K	44,0	1117,6	0,37	168
A44K	46,0	1168,4	0,38	172
A45K	47,0	1193,8	0,40	181
A46K	48,0	1219,2	0,40	181
A47K	49,0	1244,6	0,41	186
A48K	50,0	1270,0	0,42	191
A50K	52,0	1320,8	0,43	195
A51K	53,0	1346,2	0,43	195
A52K	54,0	1371,6	0,44	200
A53K	55,0	1397,0	0,45	204
A54K	56,0	1422,4	0,45	204
A55K	57,0	1447,8	0,46	209
A56K	58,0	1473,2	0,46	209
A57K	59,0	1498,6	0,47	213
A58K	60,0	1524,0	0,47	213
A59K	61,0	1549,4	0,47	213
A60K	62,0	1574,8	0,48	218
A61K	63,0	1600,2	0,48	218
A62K	64,0	1625,6	0,49	222
A63K	65,0	1651,0	0,52	236
A64K	66,0	1676,4	0,53	240
A66K	68,0	1727,2	0,54	245
A68K	70,0	1778,0	0,56	254
A70K	72,0	1828,8	0,59	268
A71K	73,0	1854,2	0,59	268
A75K	77,0	1955,8	0,59	268
A78K	80,0	2032,0	0,60	272
A80K	82,0	2082,8	0,61	277
A85K	87,0	2209,8	0,65	295
A90K	92,0	2336,8	0,69	313
A96K	98,0	2489,2	0,73	331
A105K	107,0	2717,8	0,79	358

Perfil B

B35K	38,0	965,2	0,43	195
B38K	41,0	1041,4	0,57	259
B40K	43,0	1092,2	0,68	308
B42K	45,0	1143,0	0,70	318
B44K	47,0	1193,8	0,72	327
B46K	49,0	1244,6	0,74	336
B48K	51,0	1295,4	0,75	340
B50K	53,0	1346,2	0,76	345
B51K	54,0	1371,6	0,76	345
B52K	55,0	1397,0	0,77	349

Número da correia	Circunf. Externa (pol)	Circunf. Externa (mm)	Peso (lb)	Peso (g)
B53K	56,0	1422,4	0,77	349
B54K	57,0	1447,8	0,78	354
B55K	58,0	1473,2	0,78	354
B56K	59,0	1498,6	0,78	354
B57K	60,0	1524,0	0,79	358
B58K	61,0	1549,4	0,79	358
B59K	62,0	1574,8	0,79	358
B60K	63,0	1600,2	0,80	363
B61K	64,0	1625,6	0,80	363
B62K	65,0	1651,0	0,80	363
B63K	66,0	1676,4	0,82	372
B64K	67,0	1701,8	0,84	381
B65K	68,0	1727,2	0,85	386
B66K	69,0	1752,6	0,86	390
B68K	71,0	1803,4	0,88	399
B70K	73,0	1854,2	0,90	408
B71K	74,0	1879,6	0,91	413
B75K	78,0	1981,2	0,92	417
B78K	81,0	2057,4	0,93	423
B80K	83,0	2108,2	0,96	435
B81K	84,0	2133,6	1,01	458
B83K	86,0	2184,4	1,05	476
B85K	88,0	2235,2	1,07	485
B90K	93,0	2362,2	1,12	508
B93K	96,0	2438,4	1,12	508
B95K	98,0	2489,2	1,30	590
B97K	100,0	2540,0	1,32	599
B100K	103,0	2616,2	1,35	612
B103K	106,0	2692,4	1,35	612
B105K	108,0	2743,2	1,36	617
B108K	111,0	2819,4	1,36	617
B112K	115,0	2921,0	1,37	621
B120K	123,0	3124,2	1,47	667
B124K	127,0	3225,8	1,62	735
B128K	131,0	3327,4	1,72	780
B136K	139,0	3530,6	1,74	789
B144K	147,0	3733,8	1,91	866
B158K	161,0	4089,4	1,99	903
B173K	176,0	4470,4	2,55	1157
B195K	198,0	5029,2	2,65	1202

Perfil C

C68K	72,0	1828,8	1,60	726
C75K	79,0	2006,6	1,74	789
C81K	85,0	2159,0	1,87	848
C85K	89,0	2260,6	1,99	903
C90K	94,0	2387,6	2,08	943
C96K	100,0	2540,0	2,13	966
C100K	104,0	2641,6	2,29	1039
C105K	109,0	2768,6	2,47	1120
C112K	116,0	2946,4	2,58	1170
C120K	124,0	3149,6	2,74	1243
C128K	132,0	3352,8	2,91	1320
C136K	140,0	3556,0	3,00	1361
C144K	148,0	3759,2	3,55	1610
C158K	162,0	4114,8	3,60	1633
C162K	166,0	4216,4	3,68	1669
C173K	177,0	4495,8	3,91	1774
C180K	184,0	4673,6	4,05	1837
C195K	199,0	5054,6	4,36	1978

Obs.: As medidas dos perfis Power Cable são exatamente iguais às medidas das correias Hi Power II.